

PNEUMATIC TORQUE WRENCH (HTE)



Accessories



Sliding Reaction Arms

- Modify the reaction location to access bolts with variable pitches.
- Adjustable from 10.2 cm to 30.5 cm (4" to 12") from center of spline

Nose Extensions

- Access deep bolts • 15.30 & 45cm (6", 12" & 18")

Filter Regulator Lubricator (FRL)

Recommended for use with all PTW pneumatic torque wrenches. Provides clean, lubricated air and allows for air pressure adjustment. Filter Regulator Lubricator (FRL) Recommended for use with all PTW pneumatic torque wrenches. Provides clean, lubricated air and allows for air pressure adjustment.

Model	Min Torque (Nm)	Max Torque (Nm)	S	D	L	H1	H2	R1	R2	Weight (Kg)	Max Speed (rpm)
HTE-05	100	500	3/4"	60	170	70	185	56	99	4	50
HTE-10	150	1000	3/4"	74	250	70	185	62	112	4.8	28
HTE-15	200	1500	1"	76	260	70	185	70	130	5.2	21
HTE-20	300	2000	1"	76	260	70	185	70	130	5.5	15
HTE-30	500	3000	1"	93	340	70	185	80	150	7.5	10
HTE-40	700	4000	1"	97	340	70	185	80	150	9.5	7
HTE-60	1000	6000	1-1/2"	105	380	70	185	93	158	14	5
HTE-80	2000	8000	1-1/2"	113	380	70	185	93	158	18	4